# **Safety Data Sheet**

#### **Aeroseal Adhesive**

Date of Issue: 01/01/2020

# 1 Identification

· Product identifier

· Trade name: Aeroseal Adhesive

• Manufacturer/Supplier: Aeroflex USA, Inc. 282 Industrial Park, Rd., Sweetwater, TN 37874 Phone: Toll Free 866-Aerocel (237-6235)

Emergency telephone number:

ChemTel Inc.

1-800-255-3924 (North America)

+1-813-248-0585 (International)

# 2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Repr. 2 H361 Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:







GHS02 GHS07 GHS08

Signal word: Danger

· Hazard statements:

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

(Cont'd. on page 2)



(Cont'd. of page 1)

H304 May be fatal if swallowed and enters airways.

Precautionary statements: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. P233 P240 Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. P241 Use only non-sparking tools. P242 P243 Take precautionary measures against static discharge. Do not breathe mist/vapors/spray. P260 P264 Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. P271 P280 Wear protective gloves/protective clothing/eye protection. If swallowed: Immediately call a poison center/doctor. P301+P310 P331 Do NOT induce vomiting. P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. P312 Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. P332+P313 Take off contaminated clothing and wash it before reuse. P362+P364 P337+P313 If eye irritation persists: Get medical advice/attention. P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Other hazards There are no other hazards not otherwise classified that have been identified.

# 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· Components:					
110-54-3	n-hexane	Flam. Liq. 2, H225 Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336 Eye Irrit. 2B, H320	25-50%		
67-64-1	Acetone	Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	25-50%		
108-88-3		Flam. Liq. 2, H225  Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336	10-25%		
1309-48-4	Magnesium oxide		<2.5%		

· Additional information:

(Cont'd. on page 3)

(Cont'd. of page 2)

For the wording of the listed Hazard Statements, refer to section 16.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

#### 4 First-aid measures

# Description of first aid measures

#### After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

#### After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### After eve contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

#### After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting: immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

# Most important symptoms and effects, both acute and delayed:

Headache

Dizziness

Breathing difficulty

Gastric or intestinal disorders

#### Danger:

Danger of convulsion.

Danger of disturbed cardiac rhythm.

Danger of impaired breathing.

#### Indication of any immediate medical attention and special treatment needed:

If swallowed, gastric irrigation with added, activated carbon.

Medical supervision for at least 48 hours.

# 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

Carbon dioxide

Fire-extinguishing powder

Foam

Water fog / haze

- For safety reasons unsuitable extinguishing agents: Waterstream.
- Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

(Cont'd. on page 4)



(Cont'd. of page 3)

Wear fully protective suit.

Additional information: Cool endangered containers with water fog.

#### 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

**Environmental precautions** 

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up

Allow to solidify. Pick up mechanically.

Clean the affected area carefully; suitable cleaners are:

Organic solvent

Warm water and cleansing agent

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

- · Handling
- Precautions for safe handling:

Open and handle receptacle with care.

Use only in well ventilated areas.

Keep out of reach of children.

Information about protection against explosions and fires:

Protect from heat.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Specific end use(s) No relevant information available.

### 8 Exposure controls/personal protection

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

(Cont'd. on page 5)



		(Cont'd. of page 4
110-54-3 n-hex	ane	(Conta. or page 4
PEL (USA)	Long-term value: 1800 mg/m³, 500 ppm	
REL (USA)	Long-term value: 180 mg/m³, 50 ppm	
TLV (USA)	Long-term value: 176 mg/m³, 50 ppm Skin; BEI	
EL (Canada)	Long-term value: 20 ppm Skin	
EV (Canada)	Long-term value: 176 mg/m³, 50 ppm	
LMPE (Mexico)	Long-term value: 50 ppm PIEL, IBE	
67-64-1 Aceton	e	
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm	
REL (USA)	Long-term value: 590 mg/m³, 250 ppm	
TLV (USA)	Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI	
EL (Canada)	Short-term value: 500 ppm Long-term value: 250 ppm	
EV (Canada)	Short-term value: 750 ppm Long-term value: 500 ppm	
LMPE (Mexico)	Short-term value: 750 ppm Long-term value: 500 ppm A4, IBE	
108-88-3 Tolue	·	
PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500*ppm *10-min peak per 8-hr shift	
REL (USA)	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm	
TLV (USA)	Long-term value: 75 mg/m³, 20 ppm BEI	
EL (Canada)	Long-term value: 20 ppm R	
EV (Canada)	Long-term value: 20 ppm	
LMPE (Mexico)	Long-term value: 20 ppm A4, IBE	
1309-48-4 Magı	nesium oxide	
PEL (USA)	Long-term value: 15* mg/m³ fume; *total particulate	
TLV (USA)	Long-term value: 10* mg/m³ *as inhalable fraction	
EL (Canada)	Short-term value: 10** mg/m³ Long-term value: 10* 3** mg/m³ *inhalable fume;**respirable dust and fume	
EV (Canada)	Long-term value: 10 mg/m³	
		(Cont'd. on page 6



(Cont'd. of page 5)

inhalable

LMPE (Mexico) Long-term value: 10\* mg/m<sup>3</sup> A4, \*fracción respirable

#### Ingredients with biological limit values:

#### 110-54-3 n-hexane

BEI (USA) 0.4 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: 2.5-Hexanedione without hydrolysis

#### 67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

#### 108-88-3 Toluene

BEI (USA) 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

# • Exposure controls

## General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Engineering controls: No relevant information available.
- Breathing equipment:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eye protection:

(Cont'd. on page 7)



(Cont'd. of page 6)



Safety glasses

· Body protection: Impervious protective clothing

9 Physical and chemical properties					
Information on basic physical and chemical properties					
Appearance:					
Form: Color:	Liquid Amber colored				
· Odor:	Mild				
Odor threshold:	Not determined.				
· pH-value:	Not determined.				
Melting point/Melting range:	Not determined. >35				
· Boiling point/Boiling range:					
· Flash point:	<23				
· Flammability (solid, gaseous):	Not applicable.				
· Auto-ignition temperature:	Not determined.				
· Decomposition temperature:	Not determined.				
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.				
· Explosion limits					
Lower:	Not determined.				
Upper:	Not determined.				
· Oxidizing properties:	Non-oxidizing.				
· Vapor pressure:	Not determined.				
· Density:					
Relative density:	0.81				
Vapor density:	Not determined.				
Evaporation rate:	Not determined.				
· Solubility in / Miscibility with					
Water:	Not miscible or difficult to mix.				
· Partition coefficient (n-octanol/wate	· Partition coefficient (n-octanol/water): Not determined.				
· Viscosity					
Dynamic:	Not determined.				
Kinematic:	Not determined.				
· Other information	No relevant information available.				

(Cont'd. on page 8)



(Cont'd. of page 7)

# 10 Stability and reactivity

- · **Reactivity:** No relevant information available.
- Chemical stability:
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

To avoid thermal decomposition, do not overheat.

Possibility of hazardous reactions

Reacts with oxygen.

Reacts with oxidizing agents.

Develops readily flammable gases / fumes.

- · Conditions to avoid No relevant information available.
- · Incompatible materials No relevant information available.
- Hazardous decomposition products

Carbon monoxide and carbon dioxide

Formaldehyde

# 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- On the skin: Irritant to skin and mucous membranes.
- On the eye: Irritating effect.
- · **Sensitization:** No sensitizing effects known.

#### · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

#### Probable route(s) of exposure:

Ingestion.

Inhalation.

Eve contact.

Skin contact.

- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- \* Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation.
- · STOT-single exposure: May cause drowsiness or dizziness.
- STOT-repeated exposure:

May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

Aspiration hazard: May be fatal if swallowed and enters airways.



(Cont'd. of page 8)

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity Toxic to aquatic life with long lasting effects.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- Additional ecological information
- **General notes:** Do not allowproduct to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No relevant information available.

# 13 Disposal considerations

- Waste treatment methods
- Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- **Uncleaned packagings**
- Recommendation: Disposal must be made according to official regulations.

# **14 Transport information**

· UN-Number

DOT, ADR, IMDG, IATA UN1133

UN proper shipping name

DOT, IATA Adhesives · ADR, IMDG **ADHESIVES** 

- Transport hazard class(es)
- DOT



3 · Class · Label 3

(Cont'd. on page 10)

Page: 10/12



# Safety Data Sheet - Aeroseal Adhesive

(Cont'd. of page 9) · ADR 3 (F1) · Class · Label 3 · IMDG, IATA · Class 3 · Label 3 · Packing group DOT, ADR, IMDG, IATA Ш · Environmental hazards Product contains environm entally hazardous substances: n-hexane Marine pollutant: Yes Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 **EMS Number:** F-E,S-E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: · DOT Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c)) Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each. · ADR Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.1.8.1) (Cont'd. on page 11)

(Cont'd. of page 10)



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· IMDG

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7)



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each /

# 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- ·SARA
- Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

110-54-3 n-hexane

108-88-3 Toluene

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

110-54-3 n-hexane

Chemicals known to cause developmental toxicity:

(Cont'd. on page 12)

Page: 12/12



# Safety Data Sheet - Aeroseal Adhesive

100.00		(Cont'd. of page 11)			
108-88-3	loluene				
· EPA (Env	rironmental Protection Agency):				
110-54-3	n-hexane	II			
67-64-1	Acetone	1			
108-88-3	Toluene	II			
· IARC (Int	ernational Agency for Research on Cancer):	·			
None of the	None of the ingredients are listed.				
· Canadiar	· Canadian Domestic Substances List (DSL):				
All ingred	ents are listed.				

# 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision May 11, 2018 / -

#### Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health Administration

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

#### · Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers