Printing date 21.04.2015 Revision: 30.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name: FILTER FAN & VENT CLEANER

· Article number: 52032,52128

• 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance / the mixture Basic cleaner

· 1.3 Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:

Highside Chemicals, Inc. 11114 Reichold Road Gulfport, MS 39503 USA Phone: (228) 896-9220

· 1.4 Emergency telephone number:

ChemTel Inc.

(800)255-3924, +1 (813)248-0585

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H400, H410.



Flam. Liq. 3 H226 Flammable liquid and vapour.



environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Skin Irrit, 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R21/22: Harmful in contact with skin and if swallowed.

Xi; Irritant

R36/38: Irritating to eyes and skin.

(Contd. on page 2)

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

(Contd. of page 1)

Xi; Sensitising

R43: May cause sensitisation by skin contact.

N; Dangerous for the environment

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R10: Flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Vapours of the product are heavier than air and may accumulate on the ground, in mines, drains or cellars with higher concentration.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H410.

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



This pictogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).







GHS02 GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labelling:

(R)-p-mentha-1,8-diene

· Hazard statements

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H410.

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280 Wear protective gloves / eye protection.

(Contd. on page 3)

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

Keep container tightly closed. P233

(Contd. of page 2)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/attention. P333+P313 P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

- · Hazard description:
- · WHMIS-symbols:

B3 - Combustible liquid

D2B - Toxic material causing other toxic effects



· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



HMIS Long Term Health Hazard Substances

None of the ingredients are listed.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.
- **Dangerous components:**

(R)-p-mentha-1,8-diene CAS: 5989-27-5 25-50% Xi R38; Xi R43; № N R50/53 EINECS: 227-813-5 Index number: 601-029-00-7 Flam. Liq. 3, H226 🚵 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; Skin Sens. 1, H317

(Contd. on page 4)

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

	(C	ontd. of page 3
CAS: 34590-94-8	(2-methoxymethylethoxy)propanol	10-25%
EINECS: 252-104-2	substance with a Community workplace exposure limit	
CAS: 68603-42-9	coconut diethanolamide	<10%
EINECS: 271-657-0	x Xi R36/38	
	Carc. Cat. 3]
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 26027-38-3	Nonylphenol Ethoxylate	<10%
NLP: 500-045-0	xn R22; xi R36/38; N R51/53	
	Aquatic Chronic 2, H411	
	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 111-42-2	2,2'-iminodiethanol	< 10%
EINECS: 203-868-0	xn R22-48/22; xi R38-41 xi R38-41	
Index number: 603-071-00-1	♦ STOT RE 2, H373	
	Eye Dam. 1, H318	
	Acute Tox. 4, H302; Skin Irrit. 2, H315	

26027-38-3 Nonylphenol Ethoxylate

• Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· After eve contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache

Breathing difficulty

Nausea

Cramp

Allergic reactions

· Hazards

Danger of impaired breathing.

Danger of convulsion.

(Contd. on page 5)

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

(Contd. of page 4)

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: None.
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Eliminate all ignition sources if safe to do so.

No further relevant information available.

Cool endangered receptacles with water fog or haze.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 6)

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

(Contd. of page 5)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:				
34590-94-8 (2	34590-94-8 (2-methoxymethylethoxy)propanol			
IOELV (EU)	Long-term value: 308 mg/m³, 50 ppm Skin			
PEL (USA)	Long-term value: 600 mg/m³, 100 ppm Skin			
REL (USA)	Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin			
TLV (USA)	Short-term value: 909 mg/m³, 150 ppm Long-term value: 606 mg/m³, 100 ppm Skin			
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm Skin			
,	Short-term value: 910 mg/m³, 150 ppm Long-term value: 605 mg/m³, 100 ppm			

· DNELs No further relevant information available.

(Contd. on page 7)

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

(Contd. of page 6)

- · PNECs No further relevant information available.
- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection: Use suitable respiratory protective device when aerosol or mist is formed.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Neoprene gloves

Nitrile rubber, NBR

· Eye protection:

Contact lenses should not be worn.



Safety glasses

- · Body protection: Solvent resistant protective clothing
- Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information.

No further relevant information available.

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

(Contd. of page 7)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid Yellow Odour: Citrus.

Odour threshold: Not determined.pH-value: Not determined.

· Change in condition

Melting point/Melting range: Not Determined.

Boiling point/Boiling range: 212 °F / 100 °C (414 °F / 212 °F)

• **Flash point**: 125 °F / 52 °C (257 °F / 126 °F) (ASTM D-93)

Flammability (solid, gaseous): Not applicable.
 Auto/Self-ignition temperature: Not determined.
 Decomposition temperature: Not determined.

· **Self-igniting:** Product is not self-igniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

Lower: 0,7 Vol % **Upper:** 14,0 Vol %

· Vapour pressure: Not determined.

• **Density at 20 °C (68 °F):** 0,93 g/cm³ (7,761 lbs/gal)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

water at 20 °C (68 °F): >20g/100g (product)

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C (68 °F): 12 mPas **Kinematic:** Not determined.

· Solvent content:

VOC content: 64,4 % **VOC (California)** 76-77 %

(Contd. on page 9)

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

(Contd. of page 8)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Flammable.

Reacts with oxidising agents.

Forms flammable gases/fumes.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

Toxic fumes may be released if heated above the decomposition point.

· 10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

Store away from oxidising agents.

- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Hydrocarbons

Nitrogen oxides

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

	rioute texicity.					
	· LD/LC50 values relevant for classification:					
ſ	5989-27-5 (R)-p-mentha-1,8-diene					
Ī	Oral	LD50	4400 mg/kg (rat)			
Ī	29911-28-2 1-(2-butoxy-1-methylethoxy)propan-2-ol					
Ī	Oral	LD50	4000 mg/kg (rat)			
İ	Dermal	LD50	>2000 mg/kg (rabbit)			

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- Sensitisation: Sensitisation possible through skin contact.
- · Subacute to chronic toxicity: Vapours have narcotic effect.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

Danger through skin adsorption.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

(Contd. on page 10)

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

(Contd. of page 9)

Toxic and/or corrosive effects may be delayed up to 24 hours.

- Sensitisation: May cause an allergic skin reaction.
- Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivity.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: Toxic for aquatic organisms
- 12.2 Persistence and degradability Moderately /partly biodegradable
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark:

Very toxic for fish

Due to mechanical actions of the product (e.g. agglutinations) damages may occur.

The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.

- · Additional ecological information:
- · General notes:

This statement was deduced from the properties of the single components.

Avoid transfer into the environment.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

(Contd. on page 11)

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

(Contd. of page 10)

SECTION 14: Transport information

· 14.1 UN-Number

· DOT, ADR, IMDG, IATA UN3082

· 14.2 UN proper shipping name

• DOT, IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. ((R)-p-mentha-1,8-diene, Nonylphenol

Ethoxylate)

ADR 3082 ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. ((R)-p-mentha-1,8-

diene, Nonylphenol Ethoxylate)

• IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. ((R)-p-mentha-1,8-diene, Nonylphenol

Ethoxylate), MARINÉ POLLUTANT

· 14.3 Transport hazard class(es)

· DOT, IMDG, IATA



• Class 9 Miscellaneous dangerous substances and articles.

· Label

· ADR



· Class 9 (M6) Miscellaneous dangerous substances and

articles.

· Label

14.4 Packing group

· DOT, ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: Yes

Symbol (fish and tree)
Special marking (ADR):
Special marking (IATA):
Symbol (fish and tree)
Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and

articles.

Danger code (Kemler): 30EMS Number: F-A,S-F

· 14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 12)

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

(Contd. of page 11)

· Transport/Additional information:

· ADR

Limited quantities (LQ)Excepted quantities (EQ)Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· Transport category 3 · Tunnel restriction code E

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

• UN "Model Regulation": ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. ((R)-p-mentha-1,8-diene, Nonylphenol

Ethoxylate), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- ·SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

111-42-2 2,2'-iminodiethanol

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65 (California):

· Chemicals known to cause cancer:

68603-42-9 coconut diethanolamide

111-42-2 2,2'-iminodiethanol

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

(Contd. on page 13)

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

	(Contd. of page 1
· Carcinogenic Categories	
EPA (Environmental Protection Agency)	
None of the ingredients are listed.	
· IARC (International Agency for Research on Cancer)	
5989-27-5 (R)-p-mentha-1,8-diene	;
111-42-2 2,2'-iminodiethanol	
· TLV (Threshold Limit Value established by ACGIH)	
111-42-2 2,2'-iminodiethanol	А
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients are listed.	
· Canada	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 1%)	
5989-27-5 (R)-p-mentha-1,8-diene	
34590-94-8 (2-methoxymethylethoxy)propanol	
National regulations:	
· Other regulations, limitations and prohibitive regulations	
· Substances of very high concern (SVHC) according to REACH, Article 57	
26027-38-3 Nonylphenol Ethoxylate	

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R22 Harmful if swallowed.

(Contd. on page 14)

Printing date 21.04.2015 Revision: 30.03.2021

Trade name: FILTER FAN & VENT CLEANER

(Contd. of page 13)

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com