
Printing date 09.04.2013

Revision: 09.03.2021

1 Identification of the substance/mixture and of the company/undertaking
· 1.1 Product identifier
· Trade name: <u>LEAK LOCK GOLD</u>
 Article number: 11001, 11002, 11004, 11016, 11128, 11550 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
· Application of the substance / the preparation Sealant
 • 1.3 Details of the supplier of the Safety Data Sheet • Manufacturer/Supplier: Highside Chemicals, Inc. 11114 Reichold Road Gulfport, MS 39503 USA Phone: (228) 896-9220
1.4 Emergency telephone number:
ChemTel Inc. (800)255-3924, +1 (813)248-0585
2 Hazards identification
Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. GHS07
STOT SE 3 H336 May cause drowsiness or dizziness.
Classification according to Directive 67/548/EEC or Directive 1999/45/EC F; Highly flammable
R11: Highly flammable.
 R67: Vapours may cause drowsiness and dizziness. Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and
literature data. The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.
 • 2.2 Label elements • Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. (Contd. on page 2)

Printing date 09.04.2013

Revision: 09.03.2021



Printing date 09.04.2013

Revision: 09.03.2021

(Contd. of page 2)

Trade name: LEAK LOCK GOLD

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64-17-5	ethanol	25-50%
EINECS: 200-578-6	🔥 F R11	
Index number: 603-002-00-5	🚸 Flam. Liq. 2, H225	
CAS: 14807-96-6	Talc (Mg3H2(SiO3)4)	25-50%
EINECS: 238-877-9		
CAS: 67-63-0	propan-2-ol	<10%
EINECS: 200-661-7	🗙 Xi R36; 👩 F R11	
Index number: 603-117-00-0		
	🚸 Flam. Liq. 2, H225	
	Type Irrit. 2, H319; STOT SE 3, H336	

· Additional information:

For the wording of the listed risk phrases refer to section 16.

Dried product contains substances which are considered nuisance dusts which require a NIOSH Breathing airborne particles or dust from mixing, spraying, sanding, grinding, etc. may cause irritation to respiratory tract.

4 First aid measures

· 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

• After skin contact:

Immediately rinse with water.

Clean with water and soap.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Dizziness

(Contd. on page 4)

Printing date 09.04.2013

Headache

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

(Contd. of page 3)

Nausea Thirst Disorientation • Hazards Condition may deteriorate with alcohol consumption. • 4.3 Indication of any immediate medical attention and special treatment needed Monitor circulation. If necessary oxygen respiration treatment. Medical supervision for at least 48 hours. Contains ethanol and isopropanol. 5 Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions. • For safety reasons unsuitable extinguishing agents: None.

• 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water spray.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources. Protect from heat. 6.2 Environmental precautions: Dilute with plenty of water. Suppress gases/fumes/haze with water haze or fog. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dilute with plenty of water. Dispose contaminated material as waste according to item 13. 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. (Contd. on page 5)

Printing date 09.04.2013

Trade name: LEAK LOCK GOLD

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Keep away from heat and direct sunlight. Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Flammable gas-air mixtures may form in empty receptacles. Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Do not store together with acids.

• Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:		
64-17-5 etha	nol	
PEL (USA)	1900 mg/m³, 1000 ppm	
REL (USA)	1900 mg/m³, 1000 ppm	
TLV (USA)	Short-term value: 1880 mg/m³, 1000 ppm	
EL (Canada)	Short-term value: 1000 ppm	
EV (Canada)	1,900 mg/m³, 1,000 ppm	
67-63-0 prop	an-2-ol	
PEL (USA)	980 mg/m³, 400 ppm	
		(Contd. on page

(Contd. of page 4)

Revision: 09.03.2021

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

	(Contd. of page 5)
REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm
	Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm
	Long-term value: 492 mg/m³, 200 ppm
	BEI
EL (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
EV (Canada)	Short-term value: 400 ppm
	Long-term value: 200 ppm
· PNECs No fu	rther relevant information available. rther relevant information available. formation: The lists valid during the making were used as basis.
· 8.2 Exposure	
	tective equipment:
	ective and hygienic measures: om foodstuffs, beverages and feed.
	emove all soiled and contaminated clothing
	before breaks and at the end of work.
	gases / fumes / aerosols.
	with the eyes and skin.
• Respiratory 	respiratory protective device in case of insufficient ventilation.
	respiratory protective device when high concentrations are present.
	piratory protection may be advisable.
Protection of	f hands:
Prote	ective gloves
Due to missi	terial has to be impermeable and resistant to the product/ the substance/ the preparation. ing tests no recommendation to the glove material can be given for the product/ the he chemical mixture.
Selection of degradation	the glove material on consideration of the penetration times, rates of diffusion and the
 Material of g The selection 	loves of the suitable gloves does not only depend on the material, but also on further marks of
	varies from manufacturer to manufacturer. As the product is a preparation of several
	he resistance of the glove material can not be calculated in advance and has therefore to be
checked prior	to the application.
	time of glove material
	eak through time has to be found out by the manufacturer of the protective gloves and has to
be observed. • Eye protectio	on'
Tight	ly sealed goggles
	(Contd. on pose 7)
	(Contd. on page 7)

Printing date 09.04.2013

Trade name: LEAK LOCK GOLD

Revision: 09.03.2021

(Contd. of page 6)

· Body protection: Protective work clothing

Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information.

No further relevant information available.

• 9.1 Information on basic physical a • General Information • Appearance:	and chemical properties
Form:	Pasty
Colour:	Gold coloured
· Odour:	Alcohol-like
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	172 °F / 78 °C
· Flash point:	59 °F / 15 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	>500 °F / 260 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not self-igniting.
[.] Danger of explosion:	Product is not explosive. However, formation of explosive a vapour mixtures are possible.
· Explosion limits:	
Lower:	3,5 Vol %
Upper:	15,0 Vol %
· Vapour pressure at 20 °C:	59 hPa
· Density at 20 °C:	1,2 g/cm³
Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
[·] Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wa	ter): Not determined.
	(Contd. on page

. -

Revision: 09.03.2021

Printing date 09.04.2013

Trade name: LEAK LOCK GOLD

	(Contd. of page
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	N
Organic solvents:	Not determined.
VOC (US EPA Method 24) 9.2 Other information	35 % No further relevant information available.
Stability and reactivity	
· 10.1 Reactivity	
[·] 10.2 Chemical stability	
 Thermal decomposition / condition 	
No decomposition if used and store	
10.3 Possibility of hazardous read	ctions
Flammable.	a product second which forms ownload a ministerion with air
	n product gases which form explosive mixtures with air.
Strong exothermic reaction with acid	(oxidizing) material. Danger of Explosion.
Develops readily flammable gases/	
• 10.4 Conditions to avoid	unes.
Keep ignition sources away - Do no	t smoke
Store away from oxidizing agents.	
	urther relevant information available.
10.6 Hazardous decomposition p	
Carbon monoxide and carbon dioxid	
Danger of forming toxic pyrolysis pr	oducts.
Toxicological information	
11.1 Information on toxicological	effects
• Acute toxicity:	
• Primary irritant effect:	akin and museus membranes
on the skin: Slight irritant effect on	
• on the eye: Slight irritant effect on e	
• Sensitization: No sensitizing effect	
• Subacute to chronic toxicity: Vap	
· Additional toxicological informat	ion: I dangers according to the calculation method of the General E
	ations as issued in the latest version:
Harmful	
Irritant	
Imiani	

(Contd. on page 9)

GHS

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

(Contd. of page 8) Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability The product is partially biodegradable. Significant residuals remain.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

This statement was deduced from the properties of the single components.

Due to available data on eliminability/decomposition and bioaccumulation potential a prolonged damage of the environment is unlikely.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.

Uncleaned packaging:

- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water only.

4 Transport information		
· 14.1 UN-Number · DOT, ADR, IMDG, IATA	UN1133	
· 14.2 UN proper shipping name		
· DOT, ADR, IMDG, IATA	Adhesives	
		(Contd. on page

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

	(Contd. of pag
14.3 Transport hazard class(es)	
DOT	
ICMMRE 2015	
Class	3 Flammable liquids.
Label	3
ADR	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group DOT, ADR, IMDG, IATA	П
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	F-E, <u>S-E</u>
14.7 Transport in bulk according to Ann MARPOL73/78 and the IBC Code	ex II of Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
 Transport category Tunnel restriction code 	2 D/E
UN "Model Regulation":	UN1133, ADHESIVES, 3, II

(Contd. on page 11)

Printing date 09.04.2013

Trade name: LEAK LOCK GOLD

Revision: 09.03.2021

(Contd. of page 10)

J	bry information	
 15.1 Safety United State SARA 	y, health and environmental regulations/legislation specific for the substance or ites (USA)	mixtu
· Section 35	55 (extremely hazardous substances):	
None of the	e ingredients is listed.	
· Section 31	3 (Specific toxic chemical listings):	
67-63-0 pro	opan-2-ol	
TSCA (Tox	kic Substances Control Act):	
All ingredier	nts are listed.	
· Proposition	n 65 (California):	
· Chemicals	s known to cause cancer:	
None of the	e ingredients is listed.	
· Chemicals	known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
· Chemicals	known to cause reproductive toxicity for males:	
	e ingredients is listed.	
64-17-5 eth	sting refers specifically to alcoholic beverage consumption and is not applicable for pro- hanol nic Categories	duct.
-	ronmental Protection Agency)	
•	e ingredients is listed.	
	rnational Agency for Research on Cancer)	
•	5 ethanol	1
	5 Talc (Mg3H2(SiO3)4)	2
	shold Limit Value established by ACGIH)	
•	5 ethanol	4
	6 Talc (Mg3H2(SiO3)4)	4
) propan-2-ol	4
	(National Institute for Occupational Safety and Health)	
	e ingredients is listed.	
	Occupational Safety & Health Administration)	
•	e ingredients is listed.	
	<u> </u>	
· Canada		
· Canada	Domestic Substances List (DSL)	

Printing date 09.04.2013

Revision: 09.03.2021

(Contd. of page 11)

Trade name: LEAK LOCK GOLD

Canadian Ingredient Disclosure list (limit 0.1%)

64-17-5 ethanol

Canadian Ingredient Disclosure list (limit 1%)

67-63-0 propan-2-ol

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

6 Othe	er information
	information is based on our present knowledge. However, this shall not constitute a guarantee for ar ific product features and shall not establish a legally valid contractual relationship.
H225 H319	e vant phrases 5 Highly flammable liquid and vapour. 9 Causes serious eye irritation. 6 May cause drowsiness or dizziness.
	Highly flammable. Irritating to eyes. Vapours may cause drowsiness and dizziness.
ADR: Interna IMDG: DOT: I IATA: GHS: G ACGIH NFPA: HMIS: WHMI SOUR SDS Chen 1305 Tamp Toll F	reviations and acronyms: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the ational Carriage of Dangerous Goods by Road) International Maritime Code for Dangerous Goods US Department of Transportation International Air Transport Association Globally Harmonized System of Classification and Labelling of Chemicals H: American Conference of Governmental Industrial Hygienists X: National Fire Protection Association (USA) : Hazardous Materials Identification System (USA) IIS: Workplace Hazardous Materials Information System (Canada) rces Prepared by: mTel Inc. 5 North Florida Avenue pa, Florida USA 33602-2902 Free North America 1-888-255-3924 Intl. +01 813-248-0573 site: www.chemtelinc.com