



Revision Number: 009.0

Issue date: 05/22/2018

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>LOCTITE SF 7625 RUST TREATMENT known as LOCTITE EXTEND 754 1GA EN</b>	<b>IDH number:</b>	160802
<b>Product type:</b>	Rust preventor	<b>Item number:</b>	75448
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	<b>Contact information:</b>	Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**WARNING:** CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A

### PICTOGRAM(S)



### Precautionary Statements

<b>Prevention:</b>	Wash affected area thoroughly after handling. Wear eye and face protection.
<b>Response:</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
<b>Storage:</b>	Not prescribed
<b>Disposal:</b>	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Barium sulfate	7727-43-7	5 - 10
2-Butoxyethanol	111-76-2	1 - 5
Propane-1,2-diol	57-55-6	1 - 5
Tannins	1401-55-4	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If symptoms persist, seek medical advice.
<b>Skin contact:</b>	Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention.
<b>Eye contact:</b>	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
<b>Ingestion:</b>	Keep individual calm. Do not induce vomiting. Get medical attention.
<b>Symptoms:</b>	See Section 11.

## 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide. Do not use high volume water jet.
<b>Special firefighting procedures:</b>	Wear self contained breathing apparatus.
<b>Unusual fire or explosion hazards:</b>	In case of fire, keep containers cool with water spray.
<b>Hazardous combustion products:</b>	Oxides of carbon. Traces of Oxides of sulfur.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow material to contaminate ground water system.
<b>Clean-up methods:</b>	Wipe up with adsorbent material (e.g. cloth, fleece).

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid skin and eye contact. Do not wear contact lenses. Wash thoroughly after handling.
<b>Storage:</b>	Keep container closed. Store in original container until ready to use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Barium sulfate	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust.	None	None
2-Butoxyethanol	20 ppm TWA	50 ppm (240 mg/m3) PEL (SKIN)	None	None
Propane-1,2-diol	None	None	10 mg/m3 TWA Aerosol.	None
Tannins	None	None	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None

<b>Engineering controls:</b>	Ensure adequate ventilation, especially in confined areas.
<b>Respiratory protection:</b>	Not normally required. Use NIOSH approved respirator if there is potential to exceed exposure limit(s).
<b>Eye/face protection:</b>	Safety goggles or safety glasses with side shields. Safety showers and eye wash stations should be available.
<b>Skin protection:</b>	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	Milky
<b>Odor:</b>	Mild
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	> 2.0
<b>Vapor pressure:</b>	24 mm hg (20 °C (68°F))
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	1.202
<b>Vapor density:</b>	1.2
<b>Flash point:</b>	Does not flash.
<b>Flammable/Explosive limits - lower:</b>	Not applicable
<b>Flammable/Explosive limits - upper:</b>	Not applicable
<b>Autoignition temperature:</b>	Not applicable
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not available.
<b>Solubility in water:</b>	Soluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	110 g/l of coating
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Traces of Oxides of sulfur.
<b>Incompatible materials:</b>	Strong acids and strong bases. Strong reducing agents. Strong oxidizing agents.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Heat, flames, sparks and other sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes

**Potential Health Effects/Symptoms**

<b>Inhalation:</b>	May cause respiratory tract irritation.
<b>Skin contact:</b>	Prolonged or repeated contact may cause irritation.
<b>Eye contact:</b>	Causes serious eye irritation.
<b>Ingestion:</b>	Not expected under normal conditions of use. Gastric disturbances.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Barium sulfate	None	Lung
2-Butoxyethanol	Oral LD50 (Rat) = 560 mg/kg Oral LD50 (Mouse) = 1.2 g/kg Oral LD50 (Rabbit) = 0.32 g/kg Oral LD50 (Rat) = 1.48 g/kg Oral LD50 (Mouse) = 1,519 mg/kg Dermal LD50 (Rabbit) = 400 mg/kg Inhalation LC50 (Rat, 4 h) = 486 ppm	Blood, Central nervous system, Irritant, Kidney, Liver
Propane-1,2-diol	Oral LD50 (Rabbit) = 18 g/kg Oral LD50 (Mouse) = 23.9 g/kg Oral LD50 (Rat) = 30 g/kg	Irritant
Tannins	None	Blood, Corrosive, Irritant, Kidney, Liver
Silica, amorphous, fumed, crystal-free	None	Nuisance dust

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Barium sulfate	No	No	No
2-Butoxyethanol	No	No	No
Propane-1,2-diol	No	No	No
Tannins	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** D005. Barium.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

#### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

#### Water Transportation (IMO/IMDG)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health

**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 2-Butoxyethanol (CAS# 111-76-2).

**CERCLA Reportable quantity:** Barium sulfate (CAS# 7727-43-7) 1,000 lbs. (454 kg)

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

#### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 9, 11

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 05/22/2018

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.