

1. Identification

Product identifier **Degreasing Solvent LV (4083-83)**

Other means of identification Not available.

Recommended use Degreaser

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Nu-Calgon
Address 2611 Schuetz Road
 St. Louis, MO 63043
 United States
Telephone 314-469-7000 / 800-554-5499
E-mail info@nucalgon.com

Emergency phone number 1-800-424-9300 (CHEMTREC)

Supplier See above.

2. Hazard identification

Physical hazards Flammable aerosols Category 1
 Gases under pressure Liquefied gas

Health hazards Serious eye damage/eye irritation Category 2A
 Germ cell mutagenicity Category 1B
 Carcinogenicity Category 1B
 Reproductive toxicity Category 2
 Specific target organ toxicity, repeated exposure Category 2

Environmental hazards Not classified.

WHMIS 2015 defined hazards Not classified

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Wash thoroughly after handling. Wear protective gloves, protective clothing, eye protection and face protection. Do not pierce or burn, even after use. Do not breathe mist or vapor.

Response IF exposed or concerned: Get medical attention.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
 Get medical attention if you feel unwell.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up.
 Keep container tightly closed.

Disposal Dispose of container in accordance with local, regional, national and international regulations.

WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/Information on ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	80-100*
Carbon dioxide		124-38-9	3-7*
Naphtha (petroleum), hydrotreated light		64742-49-0	5-10*
Toluene		108-88-3	1-5*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments	*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret. US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.
-----------------------------	--

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
Skin contact	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Ingestion	Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.
Most important symptoms/effects, acute and delayed	Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire-fighting measures

Suitable extinguishing media	Dry chemical. Foam. Carbon dioxide.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Do not discharge into lakes, streams, ponds or public waters.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces. - No smoking. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not re-use empty containers. Do not breathe vapors or spray mist. Avoid contact with eyes, skin and clothing. Pregnant or breastfeeding women must not handle this product. Use only in well-ventilated areas. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not handle or store near an open flame, heat or other sources of ignition. Do not puncture, incinerate or crush. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage.

8. Exposure controls/Personal protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	1800 mg/m ³ 750 ppm
	TWA	1200 mg/m ³ 500 ppm
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m ³ 30000 ppm
	TWA	9000 mg/m ³ 5000 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1590 mg/m ³ 400 ppm
	TWA	188 mg/m ³ 50 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Carbon dioxide (CAS 124-38-9)	STEL	15000 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
	TWA	5000 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	2380 mg/m3 1000 ppm
	TWA	1190 mg/m3 500 ppm
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3 30000 ppm
	TWA	9000 mg/m3 5000 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1590 mg/m3 400 ppm
Toluene (CAS 108-88-3)	TWA	188 mg/m3 50 ppm

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
Acetone (CAS 67-64-1)	15 minute	750 ppm
	8 hour	500 ppm
Carbon dioxide (CAS 124-38-9)	15 minute	30000 ppm
	8 hour	5000 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	15 minute	500 ppm
	8 hour	400 ppm
Toluene (CAS 108-88-3)	15 minute	60 ppm
	8 hour	50 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3
		5000 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m3
		100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3 30000 ppm
	TWA	9000 mg/m3 5000 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	400 mg/m3 100 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3 150 ppm
	TWA	375 mg/m3 100 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/L	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/L	Toluene	Urine	*
	0.02 mg/L	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines**Canada - Alberta OELs: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Impervious gloves. Confirm with reputable supplier first. PVC gloves. Neoprene. Nitrile

Other Wear suitable protective clothing. Use of an impervious apron is recommended. As required by employer code.

Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards Not applicable.

General hygiene considerations When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

9. Physical and chemical properties

Appearance	Clear Liquid
Physical state	Gas.
Form	Aerosol. Spray
Color	Not available.
Odor	Sweet, Pungent
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	Not available.
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.

Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	6.70609 lb/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	9.50390 %

10. Stability and reactivity

Reactivity	This product may react with strong oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Heat. Do not mix with other chemicals.
Incompatible materials	Acids. Strong oxidizing agents. Reducing agents. Caustics.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological information

Routes of exposure	Eye, Skin contact, Inhalation, Ingestion.
Information on likely routes of exposure	
Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. Headache. Nausea, vomiting.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Eye irritation

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 15800 mg/kg, Health Canada (HSA)
<i>Inhalation</i>		
LC50	Rat	76 mg/l/4h, Health Canada (HSA)
<i>Oral</i>		
LD50	Rat	5800 mg/kg, Health Canada (HSA)
Carbon dioxide (CAS 124-38-9)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Not available	

Components	Species	Test Results
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5610 mg/m ³ , 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA 12124 mg/kg, HSDB
<i>Inhalation</i>		
LC50	Rat	30 mg/L, 4 Hours, ECHA 28.1 mg/L, 4 Hours, ECHA 25.7 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA 5580 mg/kg, ECHA 2.6 g/kg, HSDB
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	May cause genetic defects.	
Carcinogenicity	May cause cancer. See below.	
ACGIH Carcinogens		
Benzene (CAS 71-43-2)	A1 Confirmed human carcinogen.	
California Proposition 65 - CRT: Listed date/Carcinogenic substance		
Benzene (CAS 71-43-2)		
Canada - Alberta OELs: Carcinogen category		
Benzene (CAS 71-43-2)	Confirmed human carcinogen.	
Canada - Manitoba OELs: carcinogenicity		
Benzene (CAS 71-43-2)	Confirmed human carcinogen.	
Canada - Quebec OELs: Carcinogen category		
Benzene (CAS 71-43-2)	Detected carcinogenic effect in humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Benzene (CAS 71-43-2)	Volume 29, Supplement 7, Volume 100F, Volume 120 - 1 Carcinogenic to humans.	
Toluene (CAS 108-88-3)	Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.	
Xylene (CAS 1330-20-7)	Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.	

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Benzene (CAS 71-43-2)

Cancer

US NTP Report on Carcinogens: Known carcinogen

Benzene (CAS 71-43-2)

Known To Be Human Carcinogen.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Teratogenicity

Toluene (benzene, methyl-) has caused fetotoxicity (reduced fetal weight), behavioural effects (effects on learning and memory) and hearing loss (in males). These effects have been observed in the offspring of rats exposed by inhalation to 1200 or 1800 ppm toluene. These effects were observed in the absence of maternal toxicity.

Specific target organ toxicity - single exposure

Not available.

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

See below

Ecotoxicological data**Components****Species****Test Results**

Acetone (CAS 67-64-1)

Crustacea

EC50

Daphnia

13999 mg/L, 48 Hours

Aquatic

Crustacea

EC50

Water flea (Daphnia magna)

10294 - 17704 mg/L, 48 hours

Fish

LC50

Rainbow trout,donaldson trout (Oncorhynchus mykiss)

4740 - 6330 mg/L, 96 hours

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Aquatic

Crustacea

EC50

Water flea (Daphnia pulex)

2.7 - 5.1 mg/L, 48 hours

Fish

LC50

Rainbow trout,donaldson trout (Oncorhynchus mykiss)

8.8 mg/L, 96 hours

8.8 mg/L, 96 hours

Toluene (CAS 108-88-3)

Algae

IC50

Algae

433 mg/L, 72 Hours

Crustacea

EC50

Daphnia

7.645 mg/L, 48 Hours

Aquatic

Crustacea

EC50

Water flea (Daphnia magna)

5.46 - 9.83 mg/L, 48 hours

Fish

LC50

Coho salmon,silver salmon (Oncorhynchus kisutch)

8.11 mg/L, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential**Mobility in soil**

No data available.

Mobility in general

Not available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)**Basic shipping requirements:**

UN number UN1950
 Proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)
 Hazard class Limited Quantity - US
 Packaging exceptions 306

Transportation of Dangerous Goods (TDG - Canada)**Basic shipping requirements:**


UN number UN1950
 Proper shipping name AEROSOLS, flammable
 Hazard class Limited Quantity - Canada

IATA/ICAO (Air)**Basic shipping requirements:**

UN number UN1950
 Proper shipping name Aerosols, flammable
 Hazard class 2.1

IMDG (Marine Transport)**Basic shipping requirements:**

UN number UN1950
 Proper shipping name AEROSOLS
 Hazard class 2

DOT; TDG**IATA; IMDG**

15. Regulatory information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada CEPA Schedule I: Listed substance

Benzene (CAS 71-43-2) Listed.
 Carbon dioxide (CAS 124-38-9) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Benzene (CAS 71-43-2) 1 TONNES
 Heptane (CAS 142-82-5) 1 TONNES
 Methanol (CAS 67-56-1) 1 TONNES
 Naphtha (petroleum), hydrotreated light (CAS 64742-49-0) 1 TONNES
 Toluene (CAS 108-88-3) 1 TONNES
 Xylene (CAS 1330-20-7) 1 TONNES

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Carbon dioxide (CAS 124-38-9)

Precursor Control Regulations

Acetone (CAS 67-64-1) Class B
Toluene (CAS 108-88-3) Class B

WHMIS 2015 Exemptions Not applicable

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.
Benzene (CAS 71-43-2) Listed.
Heptane (CAS 142-82-5) Listed.
Methanol (CAS 67-56-1) Listed.
Toluene (CAS 108-88-3) Listed.
Xylene (CAS 1330-20-7) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Benzene (CAS 71-43-2) Cancer
Central nervous system
Blood
Aspiration
Skin
Eye
respiratory tract irritation
Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance No

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Serious eye damage or eye irritation
Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Toluene	108-88-3	1-5*

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Benzene (CAS 71-43-2)
Methanol (CAS 67-56-1)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations See below

US - California Hazardous Substances (Director's): Listed substance

Acetone (CAS 67-64-1) Listed.
Benzene (CAS 71-43-2) Listed.
Carbon dioxide (CAS 124-38-9) Listed.
Heptane (CAS 142-82-5) Listed.
Methanol (CAS 67-56-1) Listed.
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0) Listed.
Toluene (CAS 108-88-3) Listed.
Xylene (CAS 1330-20-7) Listed.

US - Illinois Chemical Safety Act: Listed substance

Acetone (CAS 67-64-1)
Benzene (CAS 71-43-2)

Heptane (CAS 142-82-5)
Methanol (CAS 67-56-1)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US - Louisiana Spill Reporting: Listed substance

Acetone (CAS 67-64-1)	Listed.
Benzene (CAS 71-43-2)	Listed.
Heptane (CAS 142-82-5)	Listed.
Methanol (CAS 67-56-1)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

US - Michigan Critical Materials Register: Parameter number

Benzene (CAS 71-43-2)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US - Minnesota Haz Subs: Listed substance

Acetone (CAS 67-64-1)	Listed.
Benzene (CAS 71-43-2)	Listed.
Carbon dioxide (CAS 124-38-9)	Listed.
Heptane (CAS 142-82-5)	Listed.
Methanol (CAS 67-56-1)	Listed.
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

US - North Carolina Toxic Air Pollutants: Listed substance

Benzene (CAS 71-43-2)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant

Carbon dioxide (CAS 124-38-9)

US - Texas Effects Screening Levels: Listed substance

Acetone (CAS 67-64-1)	Listed.
Benzene (CAS 71-43-2)	Listed.
Carbon dioxide (CAS 124-38-9)	Listed.
Heptane (CAS 142-82-5)	Listed.
Methanol (CAS 67-56-1)	Listed.
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

US - Washington Chemical of High Concern to Children: Listed substance

Benzene (CAS 71-43-2)
Toluene (CAS 108-88-3)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)
Benzene (CAS 71-43-2)
Carbon dioxide (CAS 124-38-9)
Heptane (CAS 142-82-5)
Methanol (CAS 67-56-1)
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)
Benzene (CAS 71-43-2)
Carbon dioxide (CAS 124-38-9)
Heptane (CAS 142-82-5)
Methanol (CAS 67-56-1)
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)
Benzene (CAS 71-43-2)
Carbon dioxide (CAS 124-38-9)
Heptane (CAS 142-82-5)
Methanol (CAS 67-56-1)

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
Benzene (CAS 71-43-2)
Carbon dioxide (CAS 124-38-9)
Heptane (CAS 142-82-5)
Methanol (CAS 67-56-1)
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997
Methanol (CAS 67-56-1) Listed: March 16, 2012
Toluene (CAS 108-88-3) Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	* 2
FLAMMABILITY	4
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date	25-March-2020
Version #	02
Effective date	25-March-2020
Prepared by	Nu-Calgon Technical Service Phone: (314) 469-7000
Further information	Not available.
Other information	For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.