

SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	Spray Adhesive (4080-04)
Other means of identification	Not available
Recommended use	Adhesive
Recommended restrictions	None known.
Manufacturer	Nu-Calgon 2008 Altom Court St. Louis, MO 63146 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC)

2. Hazards Identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement
Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves. Wear eye/face protection. Avoid breathing gas. Use only outdoors or in a well-ventilated area.

Response

If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see this label). If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up. Keep container tightly closed.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information Not applicable.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	30-60
Acetone		67-64-1	10-30

Chemical name	Common name and synonyms	CAS number	%
Cyclohexane		110-82-7	10-30
Propane		74-98-6	5-10

Composition comments US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First Aid Measures

Inhalation	If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
Skin contact	If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see product label).
Eye contact	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical attention.
Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause drowsiness or dizziness. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children. Do not puncture or incinerate container. Do not store at temperatures above 49°C. Keep away from sources of ignition. No smoking.

5. Fire Fighting Measures

Suitable extinguishing media	Dry chemical. Carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. Cool containers with flooding quantities of water until well after fire is out. Firefighters should wear a self-contained breathing apparatus.
Special protective equipment and precautions for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. Cool containers with flooding quantities of water until well after fire is out. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.
Explosion data	
Sensitivity to mechanical impact	Not available.
Sensitivity to static discharge	Not available.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid breathing gas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only with adequate ventilation. Avoid breathing gas. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using do not eat or drink. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a cool, dry place out of direct sunlight. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3 300 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL TWA	750 ppm 500 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Cyclohexane (CAS 110-82-7)	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3 300 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields.
Skin protection	
Hand protection	Rubber gloves. Confirm with a reputable supplier first.
Other	Wear appropriate chemical resistant clothing. As required by employer code.
Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.
Thermal hazards	Not applicable.
General hygiene considerations	When using, do not eat, drink or smoke. Wash hands and face before breaks and immediately after handling the product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

9. Physical and Chemical Properties

Appearance	Misty spray
Physical state	Gas.
Form	Aerosol
Color	Clear to Milky white
Odor	Solvent
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	Not available.
Specific gravity	0.807 g/mL
Partition coefficient (n-octanol/water)	Not available.
Flash point	< 0.0 °F (< -17.8 °C) (Concentrate)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	40 - 50 psig @ 70°F
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Insoluble
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	> 20.5 mm ² /s (Liquid)
Other information	
Flame extension	42 in
Flammability (flash back)	Yes
Heat of combustion	42.5 kJ/g
VOC (Weight %)	65% (US federal, CARB/OTC/LADCO)

10. Stability and Reactivity

Reactivity	This product may react with strong oxidizing agents.
-------------------	--

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Avoid temperatures exceeding the flash point. Do not mix with other chemicals.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	Prolonged inhalation may be harmful. Narcotic effects.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity Narcotic effects.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	15800 mg/kg 20 ml/kg
<i>Inhalation</i>		
LC50	Mouse	44000 mg/m ³ /4H
	Rat	76 mg/l, 4 Hours 50.1 mg/l, 8 Hours 39 mg/l/4h
<i>Oral</i>		
LD50	Human	2857 mg/kg
	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	276000 ppm, 4 Hours 658 mg/l/4h
<i>Oral</i>		
LD50	Not available	
Cyclohexane (CAS 110-82-7)		
Acute		
<i>Dermal</i>		
LD50	Rat	2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 9500 ppm, 4 Hours
NOEL	Monkey	1243 mg/l, 6 Hours
<i>Oral</i>		
LD50	Mouse	813 mg/kg

Components	Species	Test Results
	Rat	8000 mg/kg
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 1442.8 mg/l, 15 Minutes
<i>Oral</i>		
LD50	Not available	
Skin corrosion/irritation	Causes skin irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not available.	
Skin sensitization	Prolonged or repeated exposure can cause drying, defatting and dermatitis.	
Germ cell mutagenicity	Non-hazardous by WHMIS/OSHA criteria.	
Mutagenicity	Non-hazardous by WHMIS/OSHA criteria.	
Carcinogenicity	Non-hazardous by WHMIS/OSHA criteria.	
ACGIH Carcinogens		
Acetone (CAS 67-64-1)		A4 Not classifiable as a human carcinogen.
US - California Proposition 65 - CRT: Listed date/Carcinogenic substance		
Benzene (CAS 71-43-2)		Carcinogenic.
Reproductive toxicity	Non-hazardous by WHMIS/OSHA criteria.	
Teratogenicity	Non-hazardous by WHMIS/OSHA criteria.	
Specific target organ toxicity - single exposure	Narcotic effects.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not classified.	
Chronic effects	Prolonged inhalation may be harmful.	
Further information	Not available.	
Name of Toxicologically Synergistic Products	Not available.	

12. Ecological Information

Ecotoxicity	See below		
Components		Species	Test Results
Acetone (CAS 67-64-1)			
Crustacea	EC50	Daphnia	13999 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Cyclohexane (CAS 110-82-7)			
Algae	IC50	Algae	500 mg/L, 72 Hours
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	23.03 - 42.07 mg/l, 96 hours

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Mobility in general	Not available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.


13. Disposal Considerations

Disposal instructions	Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
US RCRA Hazardous Waste U List: Reference	
Acetone (CAS 67-64-1)	U002
Cyclohexane (CAS 110-82-7)	U056
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport Information

General	Canada: TDG Proof of Classification: In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue. If applicable, the technical name and the classification of the product will appear below.
U.S. Department of Transportation (DOT)	
Basic shipping requirements:	
UN number	UN1950
Proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Hazard class	Limited Quantity - US
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
Transportation of Dangerous Goods (TDG - Canada)	
Basic shipping requirements:	
UN number	UN1950
Proper shipping name	AEROSOLS, flammable
Hazard class	Limited Quantity - Canada
Special provisions	80, 107
IATA/ICAO (Air)	
Basic shipping requirements:	
UN number	UN1950
Proper shipping name	Aerosols, flammable
Hazard class	Limited Quantity - IATA
IMDG (Marine Transport)	
Basic shipping requirements:	
UN number	UN1950
Proper shipping name	AEROSOLS
Hazard class	Limited Quantity - IMDG

DOT; IMDG; TDG



IATA



15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Canada DSL Challenge Substances: Listed substance

Butane (CAS 106-97-8) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Butane (CAS 106-97-8) 1 TONNES

Propane (CAS 74-98-6) 1 TONNES

Canada WHMIS Ingredient Disclosure: Threshold limits

Acetone (CAS 67-64-1) 1 %

Butane (CAS 106-97-8) 1 %

Cyclohexane (CAS 110-82-7) 1 %

WHMIS status Controlled

WHMIS classification Class A - Compressed Gas, Class B - Division 5 - Flammable Aerosol, Class D - Division 2B

WHMIS labeling



US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Cyclohexane (CAS 110-82-7) 1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Cyclohexane (CAS 110-82-7) Listed.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US CWA Section 311 Hazardous Substances: Listed substance

Cyclohexane (CAS 110-82-7) Listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.

Butane (CAS 106-97-8) Listed.

Cyclohexane (CAS 110-82-7) Listed.

Propane (CAS 74-98-6) Listed.

US CAA Section 111 Volatile Organic Compounds: Listed substance

Acetone (CAS 67-64-1) Listed.

Cyclohexane (CAS 110-82-7) Listed.

US CAA Section 112(r) Accidental Release Prevention - Regulated Flammable Substance: Listed substance

Butane (CAS 106-97-8) Regulated flammable substance.

Propane (CAS 74-98-6) Regulated flammable substance.

US CAA Section 112(r) Accidental Release Prevention: Threshold quantity

Butane (CAS 106-97-8) 10000 LBS
 Propane (CAS 74-98-6) 10000 LBS

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Listed.
 Propane (CAS 74-98-6) Listed.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

US CAA Section 612 SNAP Program: Listed substance

Acetone (CAS 67-64-1) Listed.
 Butane (CAS 106-97-8) Listed.
 Propane (CAS 74-98-6) Listed.

US CAA VOCs with Negligible Photochemical Activity: Listed substance

Acetone (CAS 67-64-1) Listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - No
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Cyclohexane	110-82-7	10-30

Other federal regulations

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Hazardous Substances (Director's): Listed substance

Acetone (CAS 67-64-1) Listed.
 Butane (CAS 106-97-8) Listed.
 Cyclohexane (CAS 110-82-7) Listed.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Benzene (CAS 71-43-2) Listed.

US - Illinois Chemical Safety Act: Listed substance

Acetone (CAS 67-64-1) Listed.
 Butane (CAS 106-97-8) Listed.
 Cyclohexane (CAS 110-82-7) Listed.
 Propane (CAS 74-98-6) Listed.

US - Louisiana Spill Reporting: Listed substance

Acetone (CAS 67-64-1) Listed.
 Butane (CAS 106-97-8) Listed.
 Cyclohexane (CAS 110-82-7) Listed.
 Propane (CAS 74-98-6) Listed.

US - Minnesota Haz Subs: Listed substance

Acetone (CAS 67-64-1) Listed.
 Butane (CAS 106-97-8) Listed.
 Cyclohexane (CAS 110-82-7) Listed.
 Propane (CAS 74-98-6) Listed.

US - New Jersey RTK - Substances: Listed substance

Acetone (CAS 67-64-1) Listed.
 Butane (CAS 106-97-8) Listed.
 Cyclohexane (CAS 110-82-7) Listed.
 Propane (CAS 74-98-6) Listed.

US - New York Release Reporting: Hazardous Substances: Listed substance

Acetone (CAS 67-64-1) Listed.
 Cyclohexane (CAS 110-82-7) Listed.

US - Texas Effects Screening Levels: Listed substance

Acetone (CAS 67-64-1) Listed.
 Butane (CAS 106-97-8) Listed.
 Cyclohexane (CAS 110-82-7) Listed.
 Propane (CAS 74-98-6) Listed.

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1) Listed.
 Butane (CAS 106-97-8) Listed.
 Cyclohexane (CAS 110-82-7) Listed.
 Propane (CAS 74-98-6) Listed.

US. Pennsylvania RTK - Hazardous Substances

Acetone (CAS 67-64-1) Listed.
 Butane (CAS 106-97-8) Listed.
 Cyclohexane (CAS 110-82-7) Listed.
 Propane (CAS 74-98-6) Listed.

US. Rhode Island RTK

Acetone (CAS 67-64-1) Listed.
 Butane (CAS 106-97-8) Listed.
 Cyclohexane (CAS 110-82-7) Listed.
 Propane (CAS 74-98-6) Listed.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

24-March-2015

Effective date

24-March-2015

Expiry date

24-March-2018

Further information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000

Other information

This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

This SDS conforms to the ANSI Z400.1/Z129.1-2010 Standard.